



FABBRICA CAVI - ANTENNE - ACCESSORI TV



AMC ...100

LOW TENSION HIGH RESISTANCE CABLE FOR GATE AUTOMATIONS
FIXED INSTALLATIONS IN HUMID AND NOT PROTECTED PLACES

CU

PVC

PVC

PUR



|| A || B || C || D ||

- A INNER CONDUCTOR PLAIN COPPER
- B INSULATION POLYVINYL-CHLORIDE
- C SHEATH POLYVINYL-CHLORIDE
 - COLOUR WHITE - RAL 9003
- D SHEATH POLYURETHANE
 - COLOUR GREEN - RAL 6018

TEMPERATURE RANGE -10 °C / +70 °C

MECHANICAL DATA

	SECTION	SHEATH		WEIGHT KG/KM TOTAL
AMC 2100	2 x 1,00 mm ²	ø 4,30 ± 0,20 mm	ø 6,30 ± 0,20 mm	58,4
AMC 3100	3 x 1,00 mm ²	ø 4,60 ± 0,20 mm	ø 6,60 ± 0,20 mm	70,3
AMC 4100	4 x 1,00 mm ²	ø 5,20 ± 0,20 mm	ø 7,20 ± 0,20 mm	87,0

ELECTRICAL PROPERTIES at 20°C

	VOLTAGE		CORES RESISTANCE
	OPERATING	TEST	
AMC 2100	450/750 V.	4000 V	18,0 Ohm/Km
AMC 3100	450/750 V.	4000 V	18,0 Ohm/Km
AMC 4100	450/750 V.	4000 V	18,0 Ohm/Km

The producer reserves himself to make modification on the item without any notice.